

DEVELON

Europe

Full liner



MINI EXCAVATORS



DX10Z-7

DX17Z-7

Operating weight	kg	1165	1850
Engine power	hp/kW @ rpm	10.33/7.4 @ 2050	16.5/11.9 @ 2400
Bucket capacity (SAE)	m ³	0.024	0.04



DX27Z-7



DX35Z-7

	2730	3995
	24.8/18.5 @ 2400	24.8/18.4 @ 2400
	0.08	0.11

		DX10Z-7	DX17Z-7	DX19-7
Operating weight	kg	1165	1850	1885
Bucket capacity (SAE)	m ³	0.024	0.04	0.04
Travel speed	km/h	3.4 - 1.7	2.06 - 3.73	2.06 - 3.73
Engine model	-	Kubota D722	Kubota D902	Kubota D902
Power	hp/kW @ rpm	10.33/7.4 @ 2050	16.5/11.9 @ 2400	16.5/11.9 @ 2400
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	3400	3910	3940
Digging depth	mm	1815	2240	2340
Digging height	mm	2205	3730	3470
Length	mm	3010	3531	3837
Width	mm	1100 (730)	1290 (994)	1290 (994)
Height	mm	2220	2320	2275



DX19-7

1885

16.5/11.9 @ 2400

0.04



DX25Z-7

2691

24.8/18.5 @ 2600

0.07



DX50Z-7

5438

48.8/36.4 @ 2200

0.16



DX55R-7

5740

48.8/36.4 @ 2200

0.16

DX25Z-7	DX27Z-7	DX35Z-7	DX50Z-7	DX55R-7
---------	---------	---------	---------	---------

2691

2730

3995

5438

5740

0.07

0.08

0.11

0.16

0.16

2.38 - 4.35

2.5 - 4.3

2.4 - 4.2

2.6 - 4.4

2.6 - 4.4

Kubota
D1305

Kubota
V1505

Develon D17

Develon
D18

Develon
D18

24.8/18.5
@ 2600

24.8/18.5
@ 2300

24.8/18.4
@ 2400

48.8/36.4
@ 2200

48.8/36.4
@ 2200

Stage V

Stage V

Stage V

Stage V

Stage V

4725

4845

5355

5945

6090

2695

2845

3275

3480

3630

4290

4515

5095

5575

5680

4170

4190

4760

5386

5400

1554

1550

1700

1980

1980

2452

2442

2479

2575

2575

MINI EXCAVATORS

Operating weight	kg
Engine power	hp/kW @ rpm
Bucket capacity (SAE)	m ³



DX63-7

Operating weight	kg	6218
Engine power	hp/kW @ rpm	65/44.3 @ 2300
Bucket capacity (SAE)	m ³	0.175

DX62R-7

Operating weight	kg	6216
Bucket capacity (SAE)	m ³	0.175
Travel speed	km/h	2.8 - 4.7
Engine model	-	Develon D24
Power	hp/kW @ rpm	65/44.3 @ 2300
Emission standard	-	Stage V
Digging reach	mm	6610
Digging depth	mm	4095
Digging height	mm	6025
Length	mm	5631
Width	mm	1980
Height	mm	2575



DX62R-7

6216

65/44.3
@ 2300

0.175



DX85R-7

9528

65/48.5 @ 2100

0.28

DX63-7

6218

0.175

2.8 - 4.7

Develon
D24

65/44.3
@ 2300

Stage V

6440

4095

6025

5571

1980

2575

DX85R-7

9528

0.28

2.7 - 4.7

Develon
D24

65/48.5
@ 2100

Stage V

7530

4670

7035

6450

2250

2657

WHEELED EXCAVATORS



DX57W-7

DX100W-7

Operating weight	kg	6015 - 6700	10500 - 11500
Engine power	hp/kW @ rpm	52.3/42.5 @ 2400	100/75 @ 2000
Bucket capacity (SAE)	m ³	0.175	0.3



DX165WR-7K



DX170W-7K

		17300 - 18000	17500 - 19000
		137/102 @ 2200	152/114 @ 2000
		0.7	0.75

		DX57W-7	DX100W-7	DX140W-7K
Operating weight	kg	6015 - 6700	10500 - 11500	15700 - 17500
Bucket capacity (SAE)	m ³	0.175	0.3	0.6
Travel speed	km/h	10 - 30	5.4 - 37.4	3.5 - 37
Engine model	-	Develon D24	Develon D34	Develon DL06V
Power	hp/kW @ rpm	52.3/42.5 @ 2400	100/75 @ 2000	152/114 @ 2000
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	6108	7820	7585
Digging depth	mm	3495	4245	4490
Digging height	mm	5976	8265	8195
Length	mm	5896	5713	8043
Width	mm	1947	2450	2495
Height	mm	2861	3011	3052
Arm length	mm	1600	2250	2100



DX140W-7K

15700 - 17500

152/114 @ 2000

0.6



DX160W-7K

16300 - 18000

152/114 @ 2000

0.7



DX190W-7K

19000 - 21000

174/130 @ 1900

0.8



DX210W-7K

21500 - 22500

189/141 @ 1900

0.9

DX160W-7K DX165WR-7K DX170W-7K DX190W-7K DX210W-7K

16300 - 18000 17300 - 18000 17500 - 19000 19000 - 21000 21500 - 22500

0.7

0.7

0.75

0.8

0.9

3.5 - 37

3 - 34

3.0 - 37

3.5 - 37

4.0 - 35

Develon DL06V

Perkins 1204J

Develon DL06V

Develon DL06V

Develon DL06V

152/114
@ 2000

137/102
@ 2200

152/114
@ 2000

174/130
@ 1900

189/141
@ 1900

Stage V

Stage V

Stage V

Stage V

Stage V

8235

8235

8875

9255

9980

5020

5020

5315

5725

6160

8850

8850

9140

9440

10140

8205

8205

8644

8867

9477

2495

2490

2530

2530

2495

3052

3102

3087

3131

3155

2500

2500

2500

2600

3000

CRAWLER EXCAVATORS



DX140LCR-7 DX140LC-7

Operating weight	kg	15500	14400
Engine power	hp/kW @ rpm	115/86 @ 2000	115/86 @ 2000
Bucket capacity (SAE)	m ³	0.75	0.75



DX210LC-7



DX210NLC-7

	21700	21700
	166/124 @ 1800	166/124 @ 1800
	1.2	1.2

DX140LCR-7 DX140LC-7 DX160LC-7HT

Operating weight	kg	15500	14400	16800
Bucket capacity (SAE)	m ³	0.75	0.75	0.8
Travel speed	km/h	2.9 - 4.7	2.9 - 4.7	2.3 - 3.7
Engine model	-	Develon G2 D34	Develon G2 D34	Develon G2 D34
Power	hp/kW @ rpm	115/86 @ 2000	115/86 @ 2000	115/86 @ 2000
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	8285	8285	8285
Digging depth	mm	5485	5635	5635
Digging height	mm	9265	8660	8660
Length	mm	7360	7685	7685
Width	mm	2590	2590	2590
Height	mm	2835	2785	2785
Arm length	mm	2500	2500	2500



DX160LC-7HT

16800

115/86 @ 2000

0.8



DX210-7

21300

166/124 @ 1800

1.1



DX225LC-7 & 7X

23300

174/129 @ 1800

1.3



DX230LC-9

23600

141/189 @ 1700

1.2

DX210-7

DX210LC-7

DX210NLC-7

DX225LC-7 & 7X

DX230LC-9

21300

21700

21700

23300

23600

1.1

1.2

1.2

1.3

1.2

3.2 - 5.9

3.2 - 5.9

3.2 - 5.9

3.1 - 5.5

3.1 - 5.3

Develon DL06V Develon DL06V

Develon DL06V

Develon DL06V

DX 05 V

166/124 @ 1800

166/124 @ 1800

166/124 @ 1800

174/129 @ 1800

141/189 @ 1700

Stage V

Stage V

Stage V

Stage V

Stage V

9535

9535

9535

9865

9895

6270

6270

6270

6590

6620

9330

9330

9330

9620

9535

9445

9445

9445

9570

9580

2800

2990

2540

2990

2990

3139

3139

3139

3005

3100

2600

2600

2600

2900

2900

CRAWLER EXCAVATORS



DX235LC-7

Operating weight	kg	23000
Engine power	hp/kW @ rpm	174/129 @ 1800
Bucket capacity (SAE)	m ³	1.4



DX245NHD-7

	25100	
	174/129 @ 1800	
	1.3	



DX255LC-7

	25700	
	189/141.3 @ 1900	
	1.5	

		DX235LC-7	DX235LCR-7
Operating weight	kg	23000	24300
Bucket capacity (SAE)	m ³	1.4	1.4
Travel speed	km/h	3.0 - 5.3	3.2 - 5.8
Engine model	-	Develon DL06V	Develon DL06V
Power	hp/kW @ rpm	174/129 @ 1800	174/129 @ 1800
Emission standard	-	Stage V	Stage V
Digging reach	mm	9895	9830
Digging depth	mm	6595	6680
Digging height	mm	9555	10805
Length	mm	9522	8970
Width	mm	2990	2990
Height	mm	3139	3123
Arm length	mm	2900	2900



DX235LCR-7

24300

174/129 @ 1800

1.4



DX260LC-9

26300

171/230 @ 1900

1.4



DX300LC-7

31500

271/202 @ 1800

1.7

DX245NHD-7

DX255LC-7

DX260LC-9

DX300LC-7

25100

25700

26300

31500

1.3

1.5

1.4

1.7

3.0 - 5.3

3.2 - 5.6

3.4 - 5.8

3.0 - 5.5

Develon DL06V

Develon DL06V

DX 05 V

Develon DL08V

174/129
@ 1800

189/141.3
@ 1900

171/230
@ 1900

271/202
@ 1800

Stage V

Stage V

Stage V

Stage V

9465

10175

10175

10725

6095

6810

6810

7305

9450

9705

9705

10325

9566

10080

10080

10605

2540

3000 - 3200

3200

3000 - 3200

3190

3200

3237

3050

2400

3000

3000

3100

CRAWLER EXCAVATORS



Model		DX360LC-9
Operating weight	kg	37200
Engine power	hp/kW @ rpm	304/227 @ 1800
Bucket capacity (SAE)	m ³	1.85
Operating weight	kg	37200
Bucket capacity (SAE)	m ³	1.85
Travel speed	km/h	3.5-6
Engine model	-	Develon DX08
Power	hp/kW @ rpm	304/227 @ 1800
Emission standard	-	Stage V
Digging reach	mm	10980
Digging depth	mm	7540
Digging height	mm	10325
Length	mm	11350
Width	mm	3000 - 3280
Height	mm	3390
Arm length	mm	3200



Model		DX400HD-9
Operating weight	kg	42200
Engine power	hp/kW @ rpm	336/251 @ 1800
Bucket capacity (SAE)	m ³	2.0
Operating weight	kg	42200
Bucket capacity (SAE)	m ³	2.0
Travel speed	km/h	3.2-5.6
Engine model	-	Develon DX08
Power	hp/kW @ rpm	336/251 @ 1800
Emission standard	-	Stage V
Digging reach	mm	11170
Digging depth	mm	7415
Digging height	mm	10435
Length	mm	11285
Width	mm	3000 - 3350
Height	mm	3415
Arm length	mm	3200

CRAWLER EXCAVATORS



DX420LC-7

Operating weight	kg	43500
Engine power	hp/kW @ rpm	344.4/257 @ 1800
Bucket capacity (SAE)	m ³	2.2



DX530LC-7

Operating weight	kg	52900
Engine power	hp/kW @ rpm	394/294 @ 1800
Bucket capacity (SAE)	m ³	3.3

		DX420LC-7	DX490LC-7
Operating weight	kg	43500	50400
Bucket capacity (SAE)	m ³	2.2	3.0
Travel speed	km/h	3.2 - 5.3	3.2 - 5.6
Engine model	-	Scania DC13	Scania DC13
Power	hp/kW @ rpm	344.4/257 @ 1800	394/294 @ 1800
Emission standard	-	Stage V	Stage V
Digging reach	mm	11430	12125
Digging depth	mm	7635	7790
Digging height	mm	10615	11050
Length	mm	11740	12230
Width	mm	3350	2990 - 3490 3340 - 3900
Height	mm	3355	3350
Arm length	mm	3250	3350



DX490LC-7

50400

394/294 @ 1800

3.0



DX800LC-7

79500

539/402 @ 2100

4.6



DX1000LC-7

99500

629/469 @ 2000

6.8

DX530LC-7

52900

3.3

3.2 - 5.6

Scania DC13

394/294
@ 1800

Stage V

10735

6755

9630

11530

2990 - 3490
3340 - 3900

3350

2900

DX800LC-7

79500

4.6

2.9 - 4.8

Perkins 2506

539/402
@ 2100

Stage V

11250

6685

10700

12230

3400 - 4000

3540

3350

DX1000LC-7

99500

6.8

3.2 - 5.6

Perkins 2806

629/469
@ 2000

Stage V

12430

7260

12425

11530

3440 - 4200

3615

2900



DX20ZE-7

Operating weight	kg	1941
Bucket capacity (SAE)	m ³	0,05
Travel speed	km/h	2-3,7



DX160WE-7K

Operating weight	kg	17300
Bucket capacity (SAE)	m ³	0,6
Travel speed	km/h	3,5-37

		DX20ZE-7	DX23E-7
Operating weight	kg	1941	2230/2296
Bucket capacity (SAE)	m ³	0,05	0,04
Travel speed	km/h	2-3,7	2,1-4,2
Operating time	h	5	8/10
Charging time (slow)	h	8	10/12
Charging time (fast)	h	1,5	1,5/2,5
Digging reach	mm	3975	3940
Digging depth	mm	2350	2340
Digging height	mm	3650	3470
Length	mm	3460	3860
Width	mm	1360 (950)	1290 (994)
Height	mm	2345	2270
Arm length	mm	1100	1030



DX23E-7

2230/2296

0,04

2,1-4,2



DX230LCE-7

25600

1,3

3,1-5,5



DX250LCE-7

27900

1,3

3,1-5,5

DX160WE-7K

17300

0,6

3,5-37

10

6/12

1,5

7585

4490

8195

8043

2495

3052

2100

DX230LCE-7

25600

1,3

3,1-5,5

9

8/16

2

9865

6590

9620

9570

2990

3005

2900

DX250LCE-7

27900

1,3

3,1-5,5

12

9/18

2,5

9865

6590

9620

9815

2990

3005

2900

WHEEL LOADERS



DL200-7

Operating weight	kg	12047
Engine power	hp/kW @ rpm	144/106 @ 2200
Bucket capacity (SAE)	m ³	2.0



DL220-7

	13198
	160/119 @ 2100
	2.3



DL250-7

	13847
	172/128 @ 2100
	2.5

		DL200-7	DL220-7	DL250-7
Operating weight	kg	12047	13198	13847
Bucket range (GP)	m ³	1.9 - 2.2	2.2 - 2.5	2.4 - 2.7
Engine model	-	Perkins 1204J	Develon DL06	Develon DL06
Power	hp/kW @ rpm	144/106 @ 2200	160/119 @ 2100	172/128 @ 2100
Emission standard	-	Stage V	Stage V	Stage V
Bucket capacity (SAE)	m ³	2.0	2.3	2.5
Tipping load (straight/full turn at 40°)	kg	10124/8933	10652/9383	11015/9696
Max. dump height on pivot	mm	3716	3853	3853
Breakout force	kN	98	97	116
Maximum speed	km/h	40	40	40
Turning radius at bucket	mm	5414	6016	6115
Tires	-	20.5 R25	20.5 R25	20.5 R25
Length	mm	7208	7458	7487
Width - at tires edge	mm	2539	2539	2539
Height	mm	3313	3313	3313



DL280-7 Waste Loader

Operating weight	kg	19700
Bucket range (GP)	m ³	2,8
Engine model	-	Develon DL06
Power (hp/kW @ rpm)	-	190/141 @ 2000
Emission standard	-	Stage V
Bucket capacity (SAE)	m ³	2,8
Tipping load (straight/full turn at 40°)	kg	7180/5915
Max. dump height on pivot	mm	4994
Breakout force	kN	-
Maximum speed	km/h	20
Turning radius at bucket	mm	7317
Tires	-	20.5 R25 SOLID
Length	mm	9555
Width - at tires edge	mm	2640
Height	mm	3360

WHEEL LOADERS



DL280-7

DL320-7

Operating weight	kg	15828	19493
Engine power	hp/kW @ rpm	190/141 @ 2000	271/202 @ 1800
Bucket capacity (SAE)	m ³	2.8	3.3



DL420CVT-7

DL480-7

	23990	26444
	326/240 @ 1800	345/257 @ 1800
	4.5	4.8

		DL280-7	DL320-7	DL380-7
Operating weight	kg	15828	19493	20421
Bucket range (GP)	m ³	2.7 - 3.1	3.3 - 3.8	3.7 - 4.1
Engine model	-	Develon DL06	Develon DL08	Develon DL08
Power	hp/kW @ rpm	190/141 @ 2000	271/202 @ 1800	271/202 @ 1800
Emission standard	-	Stage V	Stage V	Stage V
Bucket capacity (SAE)	m ³	2.8	3.3	3.9
Tipping load (straight/full turn at 40°)	kg	12247/10765	15948/14079	16097/14190
Max. dump height on pivot	mm	3934	4175	4175
Breakout force	kN	140	170	168
Maximum speed	km/h	40	40	40
Turning radius at bucket	mm	6182	6748	6702
Tires	-	20.5 R25	23.5 R25	23.5 R25
Length	mm	7669	8530	8309
Width - at tires edge	mm	2550	2845	2845
Height	mm	3360	3511	3511



DL380-7

20421
271/202 @ 1800
3.9



DL420-7

23990
345/257 @ 1800
4.5



DL550-7

33209
380/283 @ 1800
5.4



DL580-7

34311
400/294 @ 1800
6.0

DL420-7	DL420CVT-7	DL480-7	DL550-7	DL580-7
---------	------------	---------	---------	---------

23990	23990	26444	33209	34311
4.3 - 5.0	4.3 - 5.0	4.8 - 5.3	5.4 - 5.9	6.0 - 6.6
Scania DC13	Scania DC09	Scania DC13	Scania DC13	Scania DC13
345/257 @ 1800	326/240 @ 1800	345/257 @ 1800	380/283 @ 1800	400/294 @ 1800
Stage V	Stage V	Stage V	Stage V	Stage V
4.5	4.5	4.8	5.4	6.0
18696/16493	18696/16493	20717/18282	24830/21897	27355/24315
4265	4265	4519	4806	4996
171	171	224	230	264
40	40	40	40	40
7000	7000	7352	7573	7596
26.5 R25	26.5 R25	26.5 R25	29.5 R25	29.5 R25
8926	8926	9454	9885	10059
2982	2982	2982	3199	3199
3660	3660	3635	3863	3863

ARTICULATED DUMP TRUCKS

Maximum payload	kg
Maximum power (ISO 3046)	kW @ rpm
Body capacity heaped (without/with tailgate)	m ³



DA45-7

	41000
	368 @ 2100
	24.4/26.1

DA30-7

Speeds - forward	km/h	6 - 8 - 11 - 16 - 23 - 32 - 45 - 55
Speeds - reverse	km/h	6 - 8 - 11 - 16
Engine model	-	Scania DC9
Power	kW @ rpm	276 @ 2100
Emission standard	-	Stage V
Transmission model	-	ZF 8 EP320
Weight empty front/rear axle	kg	12700/10500
Weight loaded front/rear axle	kg	15872/35328
Net weight	kg	23200
Length	mm	9555
Width	mm	3000
Total height	mm	3572



DA30-7

28000

276 @ 2100

16.8/17.8



DA45-7 4X4

41000

368 @ 2100

25.7

DA45-7

DA45-7 4X4

5 - 8 - 11 - 16 - 23 - 32 - 45 - 55

5 - 8 - 11 - 16 - 23 - 32 - 45 - 55

5 - 8 - 11 - 16

5 - 8 - 11 - 16

Scania DC13

Scania DC13

368 @ 2100

368 @ 2100

Stage V

Stage V

ZF 8 EP420

ZF 8 EP420

14500/16000

14500/16000

22041/49059

22165/49335

30500

30500

10673

10187

3475

3975

3850

3850

SLR MACHINES



SLR and Semi-SLR

DX225LC-7 SLR

Operating weight	kg	24600
Bucket capacity (SAE)	m ³	0.45
Travel speed	km/h	3.1 - 5.5
Engine model	-	Develon DL06V
Power	hp/kW @ rpm	174/129 @ 1800
Emission standard	-	Stage V
Digging reach	mm	15365
Digging depth	mm	11660
Digging height	mm	13045
Length	mm	12390
Width	mm	3190
Height	mm	3385



DX300LC-7 SLR

DX530LC-7 Semi SLR

DX530LC-7 SLR

33000	51900	52200
0.64	1.27	0.92
3.0 - 5.5	3.2 - 5.6	3.2 - 5.6
Develon DL08P	Scania DC13	Scania DC13
271/202 @ 1800	394/294 @ 1800	394/294 @ 1800
Stage V	Stage V	Stage V
17510	16060	19615
13780	11795	15125
14195	12755	14435
14320	14155	16195
3400	3340 - 3900	3340 - 3900
3475	3910	4070

MATERIAL HANDLING MACHINES



DX160WHM-7*

Operating weight	kg	16500
Engine model	-	Deutz TCD 4.1 L4
Power (SAE J1995)	hp/kW @ rpm	140/105

DX160WHM-7*

Arm configuration	-	Straight
Operating weight	kg	16500
Travel speed	km/h	1 / 5 / 20
Engine model	-	Deutz TCD 4.1 L4
Power (SAE J1995)	hp/kW @ rpm	140/105
Emission standard	-	Stage V
Max. pin height	mm	9215
Max. working reach	mm	8610
Max. working depth	mm	3960
Boom length	mm	4,8
Arm length	mm	3,55
Min. swing radius	mm	1980
Elevating height	mm	2300



DX270WHM-7 Straight Arm

28300

Develon DL06V

189/141 @ 1900

DX180WHM-7*

DX200WHM-7*

DX270WHM-7

Straight	Straight	Straight
19400-21100	20200-21900	28300
1 / 5 / 20	1 / 5 / 20	4 / 9 / 20
Deutz TCD 4.1 L4	Deutz TCD 6.1 L6 EU Stage V	Develon DL06V
140/105	173/129	189/141 @ 1900
Stage V	Stage V	Stage V
10800	10800	12775
9800	9800	11155
1550	1150	4270
6	6	6,6
4	4	4,5
2240	2240	2855
2300	2300	2600

* Check availability with your local dealer.

MATERIAL HANDLING MACHINES



DX270WHM-7 Gooseneck Arm/Long Gooseneck

Operating weight	kg	28100/28700
Engine model	-	Develon DL06V
Power (SAE J1995)	hp/kW @ rpm	189/141 @ 1900

DX270WHM-7

Arm configuration	-	Gooseneck	Long gooseneck
Operating weight	kg	28100	28700
Travel speed	km/h	4 / 9 / 20	4 / 9 / 20
Engine model	-	Develon DL06V	Develon DL06V
Power (SAE J1995)	hp/kW @ rpm	189/141 @ 1900	189/141 @ 1900
Emission standard	-	Stage V	Stage V
Max. pin height	mm	12955	13830
Max. working reach	mm	11525	12410
Max. working depth	mm	4830	5355
Boom length	mm	6,6	7,1
Arm length	mm	5	5,4
Min. swing radius	mm	2855	2855
Elevating height	mm	2600	2600



DX350WHM-7* Gooseneck Arm

33000-38000

Deutz TCD 6.1 L6

245/180

DX300WHM-7*

DX350WHM-7*

Gooseneck

Gooseneck

28500-30800

33000-38000

1 / 5 / 20

1 / 5 / 20

Cummins QSB 6.7

Deutz TCD 6.1 L6

173/129

245/180

Stage V

Stage V

14170

15100

13590

14630

6690

4550

8

8,7

6

6,9

2800

3300

2700

2700

* Check availability with your local dealer.

TUNNELING MACHINES



Tunneling Machines

DX235RTF-7

Operating weight	kg	25689
Boom tilting angle	°	2 x 45
Travel speed	km/h	3,2 - 5,8
Engine model		Develon DL06V
Power	hp/kW @ rpm	189/141 @ 1900
Emission standard		Stage V
Digging reach	mm	9260
Digging depth	mm	5130
Digging height	mm	9900
Length	mm	9750
Width	mm	2990
Height	mm	3080

DEMOLITION MACHINES



DX140RDM-7

Configuration		Monolithic HRD	Interchangeable HRD	Interchangeable Digging
Operating weight	kg	22500	23100	22100
Travel speed	km/h	2,9 - 4,7	2,9 - 4,7	2,9 - 4,7
Engine model	-	Develon G2 D34	Develon G2 D34	Develon G2 D34
Power SAE J1995	hp/kW @ rpm	115/86 @ 1800	115/86 @ 1800	115/86 @ 1800
Emission standard	-	Stage V	Stage V	Stage V
Number of cylinders	-	4	4	4
Pin height	mm	16100	16100	-
Max tool weight	kg	1450 kg	1250 kg	-
Max GP Bucket	m ³	-	-	0.76
Track length	mm	4130	4130	4130
Transport width	mm	2590	2590	2590
Variable undercarriage width	mm	2540-3740	2540-3740	2540-3740
Overall height	mm	3020	3020	3020
Shoe width	mm	500	500	500

DEMOLITION MACHINES



Demolition Machines

		DX245DM-7	DX245DM-7
Configuration		HRD	Digging
Operating weight	kg	30800	28900
Travel speed	km/h	3.0 - 5.5	3.0 - 5.5
Engine model	-	Develon DL06P	Develon DL06P
Power (SAE J1995)	hp/kW @ rpm	173/129 @ 1800	173/129 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	12900	8170
Pin depth	mm	N/A	4785
Pin height	mm	18070	8155
Overall length	mm	11460	9590
Width superstructure	mm	2540	2540
Variable undercarriage width	mm	2540 ~ 3740	2540 ~ 3740
Overall height	mm	3150	3150



DX380DM-7

DX380DM-7

Configuration		HRD	Digging
Operating weight	kg	47400	44800
Travel speed	km/h	3.0 - 5.4	3.0 - 5.4
Engine model	-	Scania DC09	Scania DC09
Power (SAE J1995)	hp/kW @ rpm	327/240 @ 1800	327/240 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	14500	10200
Pin depth	mm	N/A	5500
Pin height	mm	23000	9200
Overall length	mm	15200	11285
Width superstructure	mm	2990	2990
Variable undercarriage width	mm	2970 ~ 4370	2970 ~ 4370
Overall height	mm	3148	3148

DEMOLITION MACHINES



Demolition Machines

		DX530DM-7	DX530DM-7
Configuration		HRD	Digging
Operating weight	kg	60500	56800
Travel speed	km/h	3.1 - 5.5	3.1 - 5.5
Engine model	-	Scania DC13	Scania DC13
Power (SAE J1995)	hp/kW @ rpm	394/294 @ 1800	394/294 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	16500	10300
Pin depth	mm	N/A	5965
Pin height	mm	27500	9690
Length	mm	18500	12230
Width	mm	2990	2990
Variable undercarriage width	mm	2970 ~ 4370	2970 ~ 4370
Height	mm	3360	3360



DX530DM-7

DX530DM-7

		HRD	Digging
Configuration		HRD	Digging
Operating weight	kg	70500	63000
Travel speed	km/h	3.1 - 5.5	3.1 - 5.5
Engine model	-	Scania DC13	Scania DC13
Power (SAE J1995)	hp/kW @ rpm	394/294 @ 1800	394/294 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	18000	10300
Pin depth	mm	N/A	5965
Pin height	mm	31000	9690
Length	mm	22300	12230
Width	mm	2990	2990
Variable undercarriage width	mm	2970 ~ 4370	2970 ~ 4370
Height	mm	3360	3360

DOZERS



Model		DD100
Operating weight	kg	11600
Engine power	hp/kW @ rpm	122/91 @ 2200
Max. traction force	t	16
Travelling Speed	km/h	9
Overall length with blade & Ripper	mm	5600
Overall length with blade only	mm	4739
Overall width (Blades width)	mm (XL/LGP)	2770/3280
XL-Version with 560-mm-shoes	cm ²	26523
LGP-Version with 710-mm-shoes	cm ²	36405



Model	DD130	
Operating weight	kg	15300
Engine power	hp/kW @ rpm	157/117 @ 2200
Max. traction force	t	22
Travelling Speed	km/h	9
Overall length with blade & Ripper	mm	6030
Overall length with blade only	mm	5035
Overall width (Blades width)	mm (XL/LGP1/LGP2)	3105/3655/3345
XL-Version with 560-mm-shoes	cm ²	33818
LGP1-Version with 710-mm-shoes	cm ²	42875
LGP2-Version with 760-mm-shoes	cm ²	45895

ATTACHMENTS

DO IT ALL!

Range of Develon Buckets, Breakers, Quick Couplers, Pallet Forks and more...

For: Develon wheel loaders, crawler and wheeled excavators.



TAKE CARE OF THE HEART OF YOUR MACHINE



Protect it with the best


DEVELON

Powered by Innovation

Find out more:



DISCOVER MORE:



HD Construction Equipment Develon Europe s.r.o.
IBC - Pobřežní 620/3, 186 00 Praha 8-Karlín
Czech Republic

©2026 HD Construction Equipment Develon Europe s.r.o.
D4600683-EN (03/26)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice.

Specification(s) for your individual Develon equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Develon units may show other than standard equipment.

DEVELON